

## PATENT

AMENDMENTS TO THE CLAIMS

Please amend the claims as indicated in the following listing of all claims:

1. (Original) A method comprising:  
extracting, from a circuit description describing a circuit, information associated with  
circuit devices connected directly to an input of the circuit, wherein the extracted  
information includes information related to device connectivity and feature sizes;  
aggregating the feature sizes of the circuit devices to obtain an aggregate feature size; and  
determining a total capacitance of the input based, at least in part, on the aggregate  
feature size.
2. (Original) The method as in claim 1, further including:  
extracting, from the circuit description, the information associated with circuit devices  
connected directly to each of a plurality of respective inputs and outputs; and  
for each of the respective inputs and outputs:  
aggregating the feature sizes of the circuit devices connected directly to the  
respective input or output to obtain an aggregate feature size; and  
determining a total capacitance of the respective input or output based, at least in  
part, on the aggregate feature size.
3. (Original) The method as in claim 1, wherein determining the total capacitance  
includes determining a capacitance of a hypothetical feature having a feature size equivalent to  
the aggregate feature size.
4. (Currently Amended) The method as in claim 1, wherein the information related to  
~~associated with~~ device connectivity includes information associated with wires connecting the  
circuit devices to the input, the method further including:  
determining an aggregate capacitance of the wires; and  
determining the total capacitance of the input based in part on the aggregate capacitance  
of the wires.

## PATENT

5. (Original) The method as in claim 1, further including providing the total capacitance of the input to a timing analysis tool.

6. (Original) The method as in claim 5 wherein the circuit description is a netlist.

7. (Original) The method as in claim 6, further including generating the netlist using a netlisting tool.

8. (Previously Presented) The method of claim 1, employed in making a computer readable medium product that encodes an integrated circuit design, the method further comprising:

identifying substantially all inputs and outputs of the circuit;

for each of the identified inputs and outputs:

performing the aggregating of the feature sizes for those of the circuit devices connected directly to the input or output to obtain an aggregate feature size; and

determining a total capacitance of the input or output based, at least in part, on the aggregate feature size;

generating an estimated timing response based on the total capacitance;

generating a circuit design using the estimated timing response; and

encoding the circuit design onto the computer readable medium product.

9. (Currently Amended) The method ~~computer-readable-medium-product~~ as in claim 8, wherein the information related to associated with device connectivity includes information associated with wires connecting the circuit devices to respective inputs and outputs, the method further comprises for each of the identified inputs and outputs:

determining an aggregate capacitance of the wires connected to the input or output; and

determining the total capacitance of the input or output based in part on the aggregate capacitance of the connected wires.

10. (Currently Amended) The method ~~computer-readable-medium-product~~ as in claim 8, wherein the computer readable medium is selected from the group consisting of a random access

## PATENT

memory, a read only memory, a magnetic tape, a magnetically encodable disk, an optically encodable tape, or an optically encodable disk, ~~or a propagated signal~~.

11. (Original) A computer readable medium tangibly embodying a program of instructions, the program of instructions comprising:

- at least one instruction executable to extract, from a circuit description describing a circuit, information associated with circuit devices connected directly to an input of the circuit, wherein the information includes information related to device connectivity and feature sizes;
- at least one instruction executable to aggregate the feature sizes of the circuit devices to obtain an aggregate feature size; and
- at least one instruction executable to determine a total capacitance of the input based, at least in part, on the aggregate feature size.

12. (Original) The computer readable medium as in claim 11, further including:

- at least one instruction executable to extract, from the circuit description, the information associated with circuit devices connected directly to each of a plurality of respective inputs and outputs;
- at least one instruction executable to aggregate the feature sizes of the circuit devices connected directly to each input or output to obtain an aggregate feature size for each input or output; and
- at least one instruction executable to determine a total capacitance of each input or output based, at least in part, on the respective aggregate feature size.

13. (Original) The computer readable medium as in claim 11, wherein the at least one instruction executable to determine the total capacitance includes at least one instruction executable to determine a capacitance of a hypothetical feature having a feature size equivalent to the aggregate feature size.

14. (Currently Amended) The computer readable medium as in claim 11, wherein the information related to ~~associated with~~ device connectivity includes information associated with

## PATENT

wires connecting the circuit devices to the input, and wherein the program of instructions further includes:

- at least one instruction executable to determine an aggregate capacitance of the wires;
- and
- at least one instruction executable to determine the total capacitance of the input based in part on the aggregate capacitance of the wires.

15. (Original) The computer readable medium as in claim 11, wherein the program of instructions further includes at least one instruction executable to provide the total capacitance of the input to a timing analysis tool.

16. (Currently Amended) The computer readable medium as in claim 11, wherein the computer readable medium is selected from the group consisting of a random access memory, a read only memory, a magnetic tape, a magnetically encodable disk, an optically encodable tape, or an optically encodable disk, or a propagated signal.

17. (Currently Amended) A method comprising:  
identifying substantially all inputs and outputs of a circuit;  
extracting, from a circuit description, information associated with circuit devices  
connected directly to the respective inputs and outputs, wherein the information  
includes information related to device connectivity and feature sizes;  
for each of the identified inputs and outputs:  
aggregating the feature sizes of the circuit devices connected directly to the input  
or output to obtain an aggregate feature size; and  
determining a total capacitance of the input or output based, at least in part, on the  
aggregate feature size.

18. (Currently Amended) The method as in claim 17, wherein the information related to  
~~associated with~~ device connectivity includes information associated with wires connecting the  
circuit devices to respective inputs and outputs, the method further comprising for each of the  
identified inputs and outputs:  
determining an aggregate capacitance of the wires connected to the input or output; and

## PATENT

determining the total capacitance of the input or output based in part on the aggregate capacitance of the connected wires.

19. (Original) The method as in claim 17, wherein determining the total capacitance includes determining a capacitance of a hypothetical feature having a feature size equivalent to the aggregate feature size.

20. (Original) The method as in claim 17, further comprising providing the total capacitance of each of the inputs and outputs to a timing analysis tool.

21. (Original) The method as in claim 17 wherein the circuit description is a netlist.

22. (Original) The method as in claim 21, further including generating the netlist using a netlisting tool.

23. (Original) A system comprising:

means for extracting, from a circuit description describing a circuit, information associated with circuit devices connected directly to an input of the circuit, wherein the information includes information related to device connectivity and feature sizes;

means for aggregating the feature sizes of the circuit devices to obtain an aggregate feature size; and

means for determining a total capacitance of the input based, at least in part, on the aggregate feature size.

24. (Original) The system as in claim 23, wherein:

the extraction means is for extracting, from the circuit description, the information associated with circuit devices connected directly to each of a plurality of respective inputs and outputs;

the aggregation means is for aggregating the feature sizes of the circuit devices connected directly to each of the plurality of inputs and outputs to obtain an aggregate feature size for each respective input and output; and

## PATENT

the determination means is for determining a total capacitance of each of the respective inputs and outputs based, at least in part, on the respective aggregate feature size.

25. (Original) The system as in claim 23, wherein the determination means includes hypothetical-feature means for determining a capacitance of a hypothetical feature having a feature size equivalent to the aggregate feature size.

26. (Currently Amended) The system as in claim 23, wherein the information related to ~~associated with~~ device connectivity includes information associated with wires connecting the circuit devices to the input and the system further includes:

wire aggregation means for determining an aggregate capacitance of the wires; and wherein the determination means is for determining the total capacitance of the input based in part on the aggregate capacitance of the wires.

27. (Original) The system as in claim 23, further including providing means for providing the total capacitance of the input to a timing analysis tool.

28. (Original) The system as in claim 23, further including a means for generating the circuit description.